



From chip seal milling operations to heavy city street cleaning, the Stewart Amos Sweeper Co.'s Starfire S-4c can handle it.

The S-4c is a heavy duty, 4.0yd³ dual engine mechanical broom street sweeper mounted on a highly maneuverable cab over chassis. No CDL is required! It's as productive as sweepers mounted on larger trucks.

Manufactured with reliability and simplicity in mind, the S-4c is built for day-in and day-out continuous duty sweeping. The short wheel base chassis creates an extremely tight turning radius making it perfect for cleaning confined city streets, cul-de-sacs, construction sites, milling jobs, and open highways.

The benefits of the Starfire S-4c include:

- Exclusive Three-Shaft Elevator Design
- Variable Height Dumping up to 11'
- Left or Right Side Hopper Dump-You Choose (select at time of purchase)
- Tight 16'9" Turning Radius
- Larger 36-Gallon Fuel Tank
- Rugged Construction
- Extremely Fuel Efficient

- Effectively Simple Electrical & Hydraulic Systems
- Ease of Maintenance
- Simplicity of Design
- Remarkably Quiet
- Safety Monitoring Camera System
- PM-10 Certified Rule 1186
- Proudly American



No CDL License Required




Exclusive 3-Shaft Elevator

BENEFITS:

LONGER LASTING. 3rd shaft ensures just the right amount of upper chain support and tension. Extends chains wear life and eliminates chain slapping.

REDUCED MAINTENANCE COSTS. 3rd shaft doubles amount of available chain adjustments. This and optimum upper chain support reduces chain wear and need to remove chain links by more than 50%.

BETTER LOADING PERFORMANCE. Maintains unrestricted debris movement. 3rd shaft maintains optimum chain spacing ensuring effective sweeping of large/bulky debris to minimize clogging.





Massive quad (4) "X" style lift scissors with four corner lift provide exceptional hopper stability especially when dumping wet, unbalanced or sticky debris.

S-4c SPECIFICATIONS



General:

Sweeping Path: 10' maximum

Debris Hopper: 4.0 cubic yards volumetric Dump Height (variable): 16" to 132"

Turning Radius*: 16' 9" Overall Length*: 19' 5"

Overall Height*: 102.5" including Strobe Lights

GVWR*: 19,500#

Main Broom:

Length: 58" Diameter: 36" Type: Chevron

Drive: Hydraulic motor/direct drive & reversible Mounting: Full floating, trailing arm, with shocks

Lift Control: Hydraulic, in-cab

Speed: Variable with auxiliary engine rpm

Dirt Shoes: Carbide, 2" wide

Dual Gutter Brooms:

Diameter: 42"

Type: Spring balanced, auto wear compensating

Drive: Hydraulic & reversible Mounting: Free-floating, trailing arm Lift Control: Hydraulic, in-cab Tilt control; in-cab (electric)

Speed: Variable with auxiliary engine rpm

Dual Float Protected

Elevator System:

Type: 7-flight squeegee with replaceable rubber edging

Liner: Bolt-in, 2 piece AR steel plates Chain: HD constant radius roller chain

Sprockets: Urethane

Shafts: Three (see side bar above) Drive: Hydraulic, in-cab, & reversible Lift Control: Hydraulic, in-cab

Elevator Jam Warning: Buzzer & light in-cab

Flushing System: Built-in

Debris Hopper:

Volumetric Capacity: 4.0 cubic yards Dump Height (variable): 16" to 132" Hopper Door Reach from Side: 44"

Inspection door, window, & safety props standard

4 Corner hopper lift

Quad (4) "X" style lift scissors

Street or curb side dump-(select at time of purchase)

Hydraulic System:

Pump: Dual tandem gear Capacity: 22 gpm @ 2000 rpm Reservoir: 40 gallons Hydraulic Oil Filter: 10 micron Oil Cooler: Electric remote mounted Integral hydraulic pressure gauges

Water Spray System:

Tank Capacity: 200 gallons Construction: Polyethylene Pump: 3.6 GPM electric diaphragm Spray Nozzles:

- 4 on front spray bar
- 2 on each gutter broom
- 4 on main broom

Fill Hose: 20' with NST coupler with anti-siphon air gap Water Pump Prefilter: 80 mesh

Electrical System:

Alternator: 120 AMP Voltage: 12 volt LED Lights: front & rear strobes; gutter brooms & rear mounted working lights; license plate; 2 stop/turn/tail; & clearance lights Backup alarm

Camera & Monitor Safety System:

7" Color monitor with right side gutter broom & rear mounted color cameras

Instrumentation & Controls:

Sweeper function rocker switches Elevator stall alarm & light Auxiliary engine hour meter & tachometer Electric throttle Console night light

Sweeper Engine:

Make: Kubota V2403-M-T-E3 T4 Interim Horsepower: 59 @ 2700 rpm Type: in-line, four-cylinder turbo diesel

Body: Standard white- high-gloss urethane enamel Undercarriage: Flat black enamel

Standard Accessories:

Auto pickup in reverse Auto shutdown for high temperature/low pressure Independent left & right gutter broom operation 36 gallon, common fuel tank Operators, parts & maintenance manuals

Limited Warranty Policy:

The Starfire S-4c sweeper is guaranteed to be free from defects due to faulty materials and/or workmanship for a period of 12 months, or 1,000 hours (whichever occurs first). Liability is limited to replacement of defect parts at factory or authorized dealer. The standard warranty of the chassis manufacturer and auxiliary engine applies.

Available Options: (not included in base price)

Arrow Board Strobe/Beacon protector Front mounted magnet Brush style dirt shoes Dual 3.6 GPM Water pumps for 7.2 GPM Epoxy Hopper liner

Stainless steel hopper Extended warranties Body paint colors

Auto Lube System Camera-dump observation

Main broom light/bulky litter debris channeler

Hopper camera-inside view Hopper Vibrator

On-Board Hi-Pressure Wash down System (w/ 50' hose & wand)

Others upon request

**Consult your dealer for details

Please read actual warranty for details and limitations

The Starfire S-4c has built a reputation for rugged, reliability and superior sweeping performance. Let us build one for you. Call your dealer today to arrange for a demonstration.

Sold & Supported Locally by:







Please Note:

Specifications are subject to change without notice

